

100%
Recycled
Nylon

Walk The Plank

Interface®



300304 Maple



300309 Hickory



300301 Beech



300305 Poplar



300308 Ash



300302 Sycamore



300306 Ginkgo



300312 Birch



300303 Cyprus



300307 Ironwood



300311 Dogwood



300310 Buckeye

Walk The Plank



300303 Cyprus

Installed: Herringbone





300301 Beech
Installed: Ashlar



300301 Beech, 300308 Ash,
300303 Cyprus & 300309 Hickory
Installed: Ashlar

Technical Specifications

Product Definition	Tufted Patterned Structured Tip Sheared Tile				
Konstruktion	Tuftgemusterte strukturierte Tip-Sheared - Schlingenqualität				
Descripción	Moqueta modular tufting bucle estructurado y pelo cortado con diseño				
Description	Dalle de moquette à velours tufté structuré, bouclé et rasé à motifs				
Type	Getufte gestructureerde tip sheared bouclé				
Descrizione	Bouclè tufted strutturato rasato				
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content				
Polfasermaterial	100% recyceltes Polyamid, enthält Anteile pre- und post-consumer recycelten Materials				
Composición Fibra	100% Poliamida reciclada BCF tintada en masa con contenido reciclado pre y post consumo				
Composition	Fibre polyamide BCF 100% recyclée teint en masse, contenant des éléments recyclés pré et post-consommation				
Poolmaterialaal	100% gerecycled Solution Dyed Polyamide BCF, bevat 100% pre- en post-consumer gerecycled content				
Fibra	100% Poliammide BCF riciclata tinta in massa con contenuto riciclato pre- e post-consumer				
Pile Yarn Weight / Poleinsatzgewicht / Peso Fibra	861g/m² ± 5%				
/ Poids de fibre / Poolinzetgewicht / Peso Felpa					
Total Weight / Gesamtgewicht / Peso Total	4824g/m² ± 5%				
Poids total / Totaalgewicht / Peso Totale					
Pile Height / Polschichtdicke / Altura Fibra / Hauteur de la fibre / Poolhoogte / Altezza Felpa	4.2 mm ± 0.3 mm				
Total Thickness / Gesamtdicke / Espesor Total / Epaisseur totale / Totale dikte / Altezza Totale	8.3 mm ± 0.5 mm				
Gauge/Ends 10 cm / Teilung x 10 cm / Galga x 10 cm / Jauge-Rangs par 10 cm / Rijen per 10 cm / Serraggio x 10 cm	1/10 – 39.4				
Tufts per m² / Noppenzahl/m² / Puntadas m² / Densité du tuft par m² / Aantal noppen per m² / Densità Punti	149,720 ± 5%				
Backing Type / Rückenkonstruktion / Soorte / Sous-couche / Ruguitvoering / Sottofondo	Graphlex®				
Wear Classification / Beanspruchungsklasse / Clasificación al tráfico / Classement Gebruiksintensiteit / Resistenza all'usura	Heavy Contract (EN 1307) Class 33 / LC2				
Style	30348				
3m² - 12 tiles per box (100 x 25 cm ± 0.2%)					
Radiant Panel / Schwerentflammbarkeit	(EN ISO 9239/1)Euroclass Bfl s1 (EN ISO 13501)				
Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)				
Dimensional Stability / Dimensionsstabilität	≤ 0.2%				
Estabilidad Dimensional / Stabilité dimensionnelle (ISO 2551 / EN 986)					
Dimensioneale stabiliteit / Test Stabilità dimensionale					
Sound Absorption					
125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
0.00	0.06	0.12	0.29	0.38	0.51

EN 14041

CE

DOP: 1037/121190

textile floor covering

EN 1307

20BEEF9A

EN 1307

Ashlar

Herringbone

27dB

≥ 2.4

≥ 7

0.20

Bfl s1

DS

<100Ω

33

Interface European Manufacturing BV reserve the right to change or modify specifications.

Die Interface European Manufacturing BV behält sich das Recht vor, Produktspezifikationen zu ändern oder entsprechend anzupassen.

Interface European Manufacturing BV se reserva el derecho a modificar las especificaciones arriba referenciadas.

Interface European Manufacturing BV se réserve la possibilité de modifier les caractéristiques ci-dessus.

Interface European Manufacturing BV behoudt zich het recht voor de specificaties te allen tijde aan te passen.

Interface European Manufacturing BV si riserva il diritto di modificare le proprie specifiche tecniche senza preavviso.

For full environment data, visit:
www.interface.com/eds
Visit our design blog at:
www.designwithpurposeblog.com

Light Value

Product	Colour No	Colour Name	L Value*	Y Value*
Walk the Plank	300301	Beech	56.8	24.7
	300302	Sycamore	26.4	4.9
	300303	Cyprus	40.2	11.4
	300304	Maple	48.8	17.4
	300305	Poplar	57.8	25.8
	300306	Ginko	49.4	17.9
	300307	Ironwood	20.3	3.1
	300308	Ash	44.7	14.3
	300309	Hickory	31.9	7.0
	300310	Buckeye	25.6	4.6
	300311	Dogwood	42.7	13.0
	300312	Birch	48.8	17.4

* **Light Value:** L Value = L according to CIE L*a*b* colour space, Y Value = Light Reflectance Value according to BS 8493

Lichtreflexionswerte: L-Wert = L gemäß CIE L*a*b* Farbspektrum, Y-Wert = Lichtreflexionswert gemäß British Standard BS 8493

Valores de Reflectancia de Luz: Valor L= L según CIE L*a*b* espacio de color, Valor Y = Valor de reflectancia de luz según el estándar británico BS 8493

Valeurs concernant la lumière: Valeur L = L faisant référence à la méthode CIE L*a*b* pour la couleur , Valeur Y = Valeurs de réflectance de la lumière selon le British Standard BS 8493

Licht waarden: L Waarde = L volgens CIE L*a*b*kleurruimte, Y Waarde = Licht Reflectie Waarde volgens BS 8493

Indici di riflettanza alla luce: Indice L= L secondo CIE L*a*b* colour space, IndiceY= Indice di riflettanza alla luce secondo la norma BS 8493

Environmental Data Sheet

Construction			
Yarn system	BCF Solution Dyed Nylon (PA6)		
Backing system	Graphlex®		
Recycled Content	Total	Pre Consumer	Post Consumer
Yarn average	100,00%	50,00%	50,00%
Product average	56,44%	47,52%	8,92%
Recycled content can be subject to differences between colours. See details for individual colours on next page.			
Carbon Footprint	Global Warming Potential (kgs CO2 equivalents/sq meter)		
Full life-cycle carbon footprint (following our EPD results or EPD calculation method)	Raw materials and Production:	8.47 kg CO ₂ eq./m ²	
	Delivery and installation:	0.53 kg CO ₂ eq./m ²	
	Use (10 years):	2.92 kg CO ₂ eq./m ²	
	End of life (waste to energy):	8.76 kg CO ₂ eq./m ²	
	TOTAL (10 years' lifetime):	20.68 kg CO ₂ eq./m ²	
CO ₂ compensation	Carbon neutral Cool Carpet® is standard		
Manufacturing			
Location	Scherpenzeel, NL		
	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990		
Installation Impacts			
TacTiles™	Optimised for glue-free installation with TacTiles™ connectors with virtually zero VOCs		
Installation Waste	In a typical installation* using the installation method below:		
	Herringbone – 3-5 % installation waste		
	Ashlar - 3-5% installation waste		
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste		
	* In a rectangular building, installed before walls.		
End-of-life			
Alternatives to landfill	Reuse: Can be cleaned and reused in a non-critical location to extend its useful life		
	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tiles		
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant		
Indoor Air Quality			
GUT (Gemeinschaft umweltfreundlicher Teppichboden)	The product passes all requirements of GUT's testing criteria regarding hazardous substances, emissions and odour.		
	GUT PRODIS certificate : Applied for		
CRI (Carpet & Rug Institute)	Compliant to LEED IQ 4.3 credit (tested in Eurofins to the equivalent test of the CRI Green Label Plus)		
Compliance to Green Building Schemes			
See next page to check how our products contribute to the main green building certification schemes (BREEAM, LEED, HQE and DGNB)			
Type III Environmental Product Declaration			
EPD according to ISO 14025	This product is covered by the Environmental Product Declaration EPD-IFF-20120021-CBD1-EN		

Recycled content – colour level						
Colourway	Total Recycled Content	Pre consumer recycled content	Post consumer recycled content	Total yarn recycled content	Yarn pre-consumer	Yarn post-consumer
300301 Beech	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300302 Sycamore	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300303 Cyprus	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300304 Maple	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300305 Poplar	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300306 Ginkgo	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300307 Ironwood	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300308 Ash	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300309 Hickory	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300310 Buckeye	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300311 Dogwood	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
300312 Birch	56,4%	47,5%	8,9%	100,00%	50,00%	50,00%
Compliance to Green Building Schemes						
BREEAM (UK and international)	BRE Green Guide Ratings: Office - Not Available Education - Not Available Health Care - Not Available Retail (by fashion) - Not Available Potential contribution to following categories and credits: Hea 02 - Indoor air quality – minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management					
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products					
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality					
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling					



TacTiles™

- A smarter, more sustainable way to install carpet tiles
- No need for liquid adhesives
- Fitting tiles is quick, clean and easy and the process virtually eliminates emissions
- No damage to sub floors, and nothing to stop you lifting or moving the carpet whenever you want



Entrance Matting

Incredibly tough, hard-wearing and practical; indoor entrance matting acts as the first line of defence to any interior by removing almost 100% of dirt, rain and mud before it's walked into your flooring.

Both of the products in our commercial entrance matting range – Barricade and Foyer – are resilient, functional, easy to maintain and stylish. And it's for these reasons that our barrier matting forms an essential part of any maintenance programme needed to keep your floorcovering looking its very best.