Interface®

Construction				
Yarn system	100% BCF PA 6			
Backing system	Graphlex®			
Recycled Content	Total	Pre-consumer recycled content	Post-consumer recycled content	
Product average	52.9%	52.9%	0.0%	
Yarn	0.0%	0.0%	0.0%	
	Recycled content can be subject	t to differences between colours. See detail	s for individual colours on next page.	
Carbon Footprint	Global Warming Potential (kgs CO2 equivalents/sq meter)			
	Raw materials and Production:	10.1 kg CO ₂ 6	eq./m²	
Full life-cycle carbon footprint	Delivery and installation:	0.65 kg CO ₂	eq./m²	
(following our EPD results or EPD calculation method)	Use (10 years):	2.85 kg CO ₂ (eq./m²	
	End of life (waste to energy):	8.18 kg CO ₂ (eq./m²	
	TOTAL (10 years' lifetime):	21.74 kg CO ₂	eq./m ²	
CO ₂ compensation	Carbon neutral Cool Carpet® is optional			
Manufacturing				
Location	Scherpenzeel, NL			
	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990			
Installation Impacts				
TacTiles™	Optimised for glue-free installation	on with TacTiles™ connectors with virtually z	ero VOCs	
Installation Waste	In a typical installation* using the installation method below:			
	Quarter turn – 3-4% installation waste			
	Monolithic - 3-4% installation waste			
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste			
	* In a rectangular building, installed before walls.			
End-of-life				
Alternatives to landfill	Reuse: Can be cleaned and reused in a non-critical location to extend its useful life			
	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tile			
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant			
Indoor Air Quality				
GuT (Gemeinschaft umweltfreundlicher Teppichboden)	The product passes all requirements of GuT's testing criteria regarding hazardous substances, emissions and odour.			
	Certificate no. 15251			
CRI (Carpet & Rug Institute)	Compliant to the requirements of the Green Label Plus programme.			
Compliance to Green Building Sch	emes			
	See next page for potential contr	ibution to various green building certification	n schemes	
Type III Environmental Product Dec	laration			
EPD according to ISO 14025	According to the EPD-IFF-2012	831-E and EPD-IFF-2012821-E for deliver	y/use/installation and end of life stages	
	According to the : EPD-IFF-201		,	

Interface®

Recycled content – colour level					
Colourway	Total recycled content %	Yarn recycled content %			
672716 Mocha					
	59.1%	0.0%			
672717 Sunflower	49.5%	0.0%			
672721 Cayenne	49.5%	0.0%			
672724 Mauve	59.1%	0.0%			
672725 Pashmina	49.5%	0.0%			
672726 Fuschia	49.5%	0.0%			
672727 Hot Pink	49.5%	0.0%			
672728 Dark Orchid	59.1%	0.0%			
672732 Blackcurrant	59.1%	0.0%			
672737 Lagoon	49.5%	0.0%			
672738 Ocean	49.5%	0.0%			
672740 Real Blue	49.5%	0.0%			
672741 Aegean Sea	49.5%	0.0%			
672742 Spring	49.5%	0.0%			
672743 Green	49.5%	0.0%			
672744 Emerald	59.1%	0.0%			
672745 Lemonade	49.5%	0.0%			
672746 Pistacchio	49.5%	0.0%			
672747 Olive	49.5%	0.0%			
672748 Jungle	59.1%	0.0%			

Interface®

Compliance to Green Building Schemes				
BREEAM (UK and international)	BRE Green Guide Ratings: Office - A rated Education - A rated Health Care - A+ rated Retail (by fashion) - A+ rated Potential contribution to following categories and credits: Hea 02 - Indoor air quality - minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management			
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products			
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality			
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling			