Interface®

Construction					
Yarn system	100% BCF PA 6.6				
Backing system	Graphlex®				
Recycled Content	Total	Pre consumer	Post consumer		
Product average	46,24%	46,24%	0,00%		
Yarn	0,00%	0,00%	0,00%		
	Recycled content can be subject	to differences between colours. S	See details for individual colours on next page.		
Carbon Footprint	Global Warming Potential (kgs Co	O2 equivalents/sq meter)			
	Raw materials and Production:	10.	0 kg CO ₂ eq./m ²		
Full life-cycle carbon footprint	Delivery and installation:	0.3	1 kg CO ₂ eq./m ²		
(following our EPD results or	Use (10 years):	2 k	2 kg CO ₂ eq./m²		
EPD calculation method)	End of life (waste to energy):	4.5	4.5 kg CO ₂ eq./m²		
	TOTAL (10 years' lifetime):	16.	81 kg CO ₂ eq./m²		
CO ₂ compensation	Carbon neutral Cool Carpet® is o	ptional			
Manufacturing					
	Scherpenzeel, NL				
Location	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990				
Installation Impacts					
TacTiles™	Optimised for glue-free installation	n with TacTiles™ connectors with	virtually zero VOCs		
Installation Waste	In a typical installation* using the installation method below:				
	Quarter turn – 3-4% installation waste				
	Monolithic - 3-4% installation waste				
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste				
	* In a rectangular building, installed before walls.				
End-of-life					
	Reuse: Can be cleaned and reuse	ed in a non-critical location to exte	end its useful life		
Alternatives to landfill	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tiles				
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant				
Indoor Air Quality					
GUT (Gemeinschaft	The product passes all requirements of GUT's testing criteria regarding hazardous substances, emissions and odour.				
umweltfreundlicher Teppichboden)					
CRI (Carpet & Rug Institute)	Compliant to the requirements of the Green Label Plus programme.				
Compliance to Green Building Sch					
,	_	products contribute to the main g	reen building certification schemes (BREEAM,		
Type III Environmental Product Dec	laration				
EPD according to ISO 14025	This product has a type III Enviror				

Interface®

					Yarn pre	Yarn post
Colourway	Total recycled content	Pre consumer recycled content	Post consumer recycled content	Yarn recycled content	consumer recycled content	consumer recycled content
5051 Zinc	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5052 Smoke	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5053 Carbon	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5054 Twilight	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5055 Silver	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5056 Dolphin	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5057 Basalt	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5058 Black	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5059 Sand	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5060 Taupe	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5061 Chocolate	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5063 Ginger	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5064 Garam Masala	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5065 Orange	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5062 Volcano	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5066 Opera	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5074 Midnight	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5069 Lobelia	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5067 Santorin	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5068 Cobalt	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5270 Blue Moon	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%
5071 Lime	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5072 Sycamore	48,18%	48,18%	0,00%	0,00%	0,00%	0,00%
5073 lvy	44,59%	44,59%	0,00%	0,00%	0,00%	0,00%

Compliance to Green Building So	Compliance to Green Building Schemes				
BREEAM (UK and international)	BRE Green Guide Ratings: Office - A rated Education - A rated Health Care - A + rated Retail (by fashion) - A+ rated Potential contribution to following categories and credits: Hea 02 - Indoor air quality - minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management				
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products				
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality				
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling				