



Interface® | HN 820


SPECIFICATION


Product definition	Tufted Patterned Structured Cut and Loop Tile	Style number	30806
Pile Material	100% Recycled Solution Dyed Nylon	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	780g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
Total Weight	4834g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	3.3 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	7.4 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (EN 986)
Gauge/Ends per 10cm	5/64 - 50.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Tufts per m²	181,440 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (25 cm x 100 cm ± 0.2%)


CE
06
0336-CPD-8538


Cfl-s1


BS


EN 1307


≤10⁹Ω



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications