




Interface® | HN 830

SPECIFICATION


Product definition	Tufted Plain Shag Cut Tile	Style number	60804
Pile Material	100% Recycled Solution Dyed Nylon	Wear Classification	EN 1307:32 Contract General
Pile Yarn Weight	1425g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
Total Weight	5274g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	8.2 mm ± 0.3 mm	Castor Chair Rating	≥ 2.0 (EN 985)
Total Thickness	12.0 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (EN 986)
Gauge/Ends per 10cm	5/32 - 25.2	Vertical Electrical Resistance	
Tufts per m²	93,240 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	10 - 2.5m ² (25 cm x 100 cm ± 0.2%)


CE
06
0336-CPD-8538









EN 1307






C793A286



30dB










32









Mission Zero:
our promise to eliminate any negative impact our company may have on the environment by the year 2020.

www.interface.com