



Interface® | HN 840


SPECIFICATION


Product definition	Tufted Patterned Structured Loop Tile	Style number	30807
Pile Material	100% Recycled Solution Dyed Nylon	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	980g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
Total Weight	4963g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	4.7 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	9.8 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (EN 986)
Gauge/Ends per 10cm	1/10 - 39.4	Vertical Electrical Resistance	≥ 7 (ISO 105/B02)
Tufts per m²	116,230 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	12 - 3m ² (25 cm x 100 cm ± 0.2%)

CE
06
0336-CPD-8538


Cfl-s1


DS


EN 1307



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com