



Interface® | Heuga 530


SPECIFICATION


| | | | |
|-----------------------------------|---------------------------------|---|---|
| Product definition | Tufted Plain Textured Loop Tile | Style number | 60530 |
| Pile Material | 100% BCF Nylon | Wear Classification | EN 1307 33 Heavy Contract |
| Pile Yarn Weight | 660g/m ² ± 5% | Radiant panel | Euroclass Bfl S1 (EN ISO 9239/1) (EN ISO 13501) |
| Effective pile yarn weight | 400g/m ² ± 10 % | Hot Metal Nut | Pass, low radius of effects of ignition (BS 4790) |
| Total Weight | 4309g/m ² ± 7,5% | Castor Chair Rating | ≥ 2,4 (EN 985) |
| Pile Height | 3,6 mm ± 0,3 mm | Dimensional Stability | ≤ 0,2% (ISO 2551 / EN 986) |
| Total Thickness | 6,8 mm ± 0,3 mm | Vertical Electrical Resistance | 5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM) |
| Gauge/Ends per 10cm | 1/10 - 39.5 | Colour Fastness - Light | 6-7 (ISO 105/B02) |
| Tufts per m² | 106,650 ± 5% | Tiles per Box | 20 - 5 m ² (50 x 50 cm ± 0,2%) |
| Backing Type | Graphlex® | | |


CE
06
0336-CPD-8538



Bfl-s1



DS



EN 1307



EN 1307



Monolithic Quarter Turn



11893



28 dB












Environmental Product Scheme
Certificate Number ENP-027


33





Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications