


# Interface®


## Northern Light

<b>Product definition</b>	Microtuft Plain Level Loop Tile					
<b>Pile Material</b>	100% Recycled Solution Dyed Nylon					
<b>Pile Yarn Weight</b>	520g/m <sup>2</sup> ± 5%					
<b>Total Weight</b>	4484g/m <sup>2</sup> ± 5%					
<b>Pile Height</b>						
<b>Total Thickness</b>	5.5 mm ± 0.5 mm					
<b>Gauge/Ends per 10cm</b>	5/64 - 50.4					
<b>Tufts per m2</b>	191.520 ± 5%					
<b>Backing Type</b>	Graphlex®					
<b>Wear Classification</b>	EN 1307 33 Heavy Contract					
<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass CfI s1 (EN ISO 13501)					
<b>Dimensional Stability</b>	≤ 0,2% (ISO 2551/EN 986)					
<b>Impact Sound Insulation (ΔLw)</b>	14 dB (EN ISO 10140-3)					
<b>Rating of Sound Absorption</b>	α <sub>w</sub> 0.15 (EN ISO 11654)					
<b>Sound Absorption</b>						
<b>125Hz</b>	<b>250Hz</b>	<b>500Hz</b>	<b>1000Hz</b>	<b>2000Hz</b>	<b>4000Hz</b>	(EN ISO 354)
0.03	0.02	0.05	0.14	0.24	0.38	α <sub>s</sub>
<b>Style number</b>	60306					5 m <sup>2</sup> - 20 Tiles per Box (25 x 100 cm ± 0.20%)


**EN 14041**




DOP: 1037/120910  
textile floor covering  
**EN 1307**




ASHLAR HERRINGBONE




33 W Cfl-s1  
14 dB 0.15




≥ 7 ≥ 2,4



7F0E8151  
www.pro-tilt.info



GUT  
GUMI  
GUMI  
GUMI



install with  
Tactiles®

Interface Europe Ltd reserve the right to change or modify specifications

[www.interface.com](http://www.interface.com)



**Mission Zero:**  
our promise to eliminate any  
negative impact our company  
may have on the environment  
by the year 2020.